

# BOXER

BIG POWER IN ALL PLACES



## WIDE RANGE of APPLICATIONS • BOTTOM LINE PRODUCTIVITY

Reduce hand labour and increase job site productivity with Boxer mini skid steers.

The Boxer 300, 400 and 500 Series are the latest in a line of innovative mini-skid steers that have once again raised the bar in the compact utility loader industry. All are tracked machines as standard, with the 400 Series also available in a wheeled version.

Their rugged power, smooth controls, and agile manoeuvrability open the way for an expanded array of attachments for a variety of industries and applications such as:

Landscaping, Rental, Construction, Concrete Work, Irrigation, Fencing, Demolition, Golf Course Maintenance and Construction, Utility Work and Municipalities to name a few.

These machines provide the strength and performance to handle a huge variety of tasks and the versatility to get into tight areas.

DAAK Engineering is the authorised distributor for Boxer products throughout Western Australia.

# SPECIFICATIONS

## 300 Series



Specifications	322	
Engine	Kubota D902	
Power	22 hp	16.4 kW
Hydraulic Pressure	3000 psi	20, 685 kPa
Hydraulic Flow	9.4 USgpm	35.55 l/min
Width	34.5 in	876 mm
Weight	1900 lbs	862 kg
Overall Height	49 in	1245 mm
Overall Length (w/out bucket)	68 in	1727 mm
Trackbase	32 in	813 mm
Tip Capacity	1325 lbs	601 kg
Travel Speed	3.5 mph	5.6 kph
Ground Clearance	5 in	127 mm
Ground Pressure	3.2 psi	22 kPa

Specifications	427 TRX	
Engine	Kohler Command Pro, air cooled	
Power	27 hp	20.1 kW
Hydraulic Pressure	3000 psi	20, 685 kPa
Hydraulic Flow	12.6 USgpm	47.69 l/min
Width	43.5 in	1105 mm
Weight	2250 lbs	1021 kg
Overall Height	50 in	1270 mm
Overall Length (w/out attachments)	70 in	1772 mm
Trackbase	37 in	927 mm
Tip Capacity	1800 lbs	816 kg
Travel Speed	3.5 mph	5.6 kph
Ground Clearance	7 in	178 mm

## 400 Series



## 500 Series



Specifications	532DX	
Engine	Kubota	
Power	32 hp	22.4 kW
Hydraulic Pressure	3000 psi	20,685 kPa
Hydraulic Flow	14.5 USgpm	54.88 l/min
Width Variable Track (min)	35 in	889 mm
Width Variable Track (max)	43.5 in	1105 mm
Weight	2470 lbs	1120 kg
Dump Height	60 in	1524 mm
Overall Length (w/out bucket)	77 in	1956 mm
Tip Capacity	2100 lbs	953 kg
Travel Speed	3.7 mph	6.0 kph
Ground Clearance	5 in	127 mm
Ground Pressure	3.7 psi	25.5 kPa

## Accessories

Here's a selection of some of the accessories available for your Boxer mini skid steer.



STANDARD BUCKET

4-IN-1 BUCKET

POWER RAKE

TRENCHER

AUGER HEAD AND BITS

HYDRAULIC BREAKER

Note: Due to a policy of constant innovation, specifications may be subject to change.



14 Clapham Street, Beckenham, Western Australia 6107  
Tel: (08) 9258 9333 Fax: (08) 9258 9111

Email: [sales@daak.com.au](mailto:sales@daak.com.au) Web: [www.daak.com.au](http://www.daak.com.au)